



REVISIONS		
ISS	ZONE	DESCRIPTION\PER REQUEST\DATE
V	OPEN	Open drawings to customers

13	BOOT	PVC	BLACK	1	
12	CAP	NYLON	BLUE	1	
11	SEAL RING	NBR	specs: $\varnothing 12 \sim \varnothing 15$ $\varnothing 8.5 \sim \varnothing 11$	1	
10	CABLE CLAMP	NYLON	GRAY	1	
9	SEAL RING	NBR	BLACK $\varnothing 19 \times L5$	1	
8	SEAL RING	SILICON	$\varnothing 20 \times 2(WH)$	1	
7	PLASTIC SHELL	NYLON	DARK GRAY	1	
6	PUSH BUTTON	ZINC	NICKEL	1	
5	PUSH BUTTON SPRING	SPRING STEEL	$\varnothing 2.4 \times \varnothing 1.8 \times 9.5$	1	
4	SPRING	H62	TIN	4	
3	SCREW M3x4.8	A3	ELECTOR- COATING BLACK	4	
2	PIN	ZINC	SILVER	4	
1	HEADER CLOCK	PA	BLACK	1	
NO.	DESCRIPTION	MATERIAL	FINISH	Q'TY	DRAWING NO.

DIMENSIONS ARE IN MILLIMETERS		APPROVED	CDG	DATE	26.10.2020
UNLESS OTHERWISE SPECIFIED TOLERANCES		CHECKED	DS	DATE	26.10.2020
ANGLES = $\pm 5^\circ$		DRAWN	JIANGZHNETAO	DATE	2020-10-13
UP TO 6 = ± 0.2		FILE NO.			
6-40 = ± 0.4		ERP LINK:	----		
40-120 = ± 0.6		THIRD_ANGLE			
120-315 = ± 1		SCALE	1/1		
ABOVE 315 = ± 1.6					

		TITLE	SPEAKER CONNECTOR WITH 4 PIN FEMALE INLINE, SILVER PLATED CONTACTS.	
PART NO.	SP24FP	REV.	A1	